

RC Connector Checkout List: Card Number _____

Checking the 50 pin J5 connector:

Put the EIC in slot 1 and the RC in slot 5. Attach a 50 pin cable to the J5 connector of each card. Log in to the **cmslab** account. Zero all the memories. Start **vmedia** and execute the **script check_j5.txt**. That will program things in the order given by the grey numbers. Place a check mark over the grey number.

RC Slot 5: Check at U125 (pin 8,11,14,17) and U126 (pins 8,11,14)

Path checked with cable:	Pattern	Okay?	Pattern	Okay?	Pattern	Okay?
WEST(Backplane): 8 paths	7F	1	00	2	7F & 7F	3

Move the RC to slot 1 and repeat the test.

RC Slot 1: Check at U125 (pin 8,11,14,17) and U126 (pins 8,11,14)

WEST(Backplane): 8 paths	7F	4	00	5	7F & 7F	6
--------------------------	----	---	----	---	---------	---

Checking the 50 pin J3 connector:

Attach a 50 pin cable to the J3 connector of each card. Execute the **script check_j3.txt**. That will program things in the order given by the grey numbers. Place a check mark over the grey number.

RC Slot 1: EISO ASIC for R0: U66: 24, 28, 4, 6

Path checked with cable:	Pattern	Okay?
SW(Backplane): 4 paths	FF	1

Move the RC to slot 0 and repeat the test.

RC Slot 0: EISO ASIC for R0: U66: 24, 28, 4, 6

SW(Backplane): 4 paths	FF	2
------------------------	----	---